


IMPORTANT INSTRUCTIONS

For Installation of LS684, LS685, LS686, Filter Support Accessories

MODELS LS684 - LS343 Refractor Gimbal Ht Glass/filter Support
 LS685 - LS343 Refractor Gimbal Linear Spreader/filter Support
 LS686 - LS343 Refractor Gimbal Dichroic Filter/filter Support


www.lumascope.com.au

A.C.N. 010 572 773




1 Open fixture

Loosen screws with allen key provided. If necessary gently lever lid out with large screwdriver. Remove components as shown.



2 Replace filter assembly


Insert new filter assembly into fixture. The glass side of the assembly should be closest to the lamp



4 Replace lens and lid

Replace Filter and lens and outer cover assembly and reseal fixture.

NOTE




Additional filter

Additional filters, (137mm x 3mm Max) can be added to the fixture by retaining beneath spring clips on the top of the secondary glass

Intentionally Left Blank

IMPORTANT

For Very Narrow Refractors -



Ensure that glare shield, if supplied - VN models only, is fitted the correct way up as shown. Glare shield should seat neatly into fixture.

LUMASCOPE CONTACT DETAILS

C957US - 2006_07_REV001

LUMASCOPE USA INC. 1300 Industrial Rd., Unit #19 San Carlos, CA 94070, USA • Free Call: 1-866-695-LUMA(5862) • Ph: 1-(650)-595-LUMA(5862) • Fax: 1-(650)-595-5820


IMPORTANT INSTRUCTIONS

For Installation of LS684, LS685, LS686, Filter Support Accessories

MODELS LS684 - LS343 Refractor Gimbal Ht Glass/filter Support
 LS685 - LS343 Refractor Gimbal Linear Spreader/filter Support
 LS686 - LS343 Refractor Gimbal Dichroic Filter/filter Support


www.lumascope.com.au

A.C.N. 010 572 773




1 Open fixture

Loosen screws with allen key provided. If necessary gently lever lid out with large screwdriver. Remove components as shown.



2 Replace filter assembly


Insert new filter assembly into fixture. The glass side of the assembly should be closest to the lamp



4 Replace lens and lid

Replace Filter and lens and outer cover assembly and reseal fixture.

NOTE




Additional filter

Additional filters, (137mm x 3mm Max) can be added to the fixture by retaining beneath spring clips on the top of the secondary glass

Intentionally Left Blank

IMPORTANT

For Very Narrow Refractors -



Ensure that glare shield, if supplied - VN models only, is fitted the correct way up as shown. Glare shield should seat neatly into fixture.

LUMASCOPE CONTACT DETAILS

C957US - 2006_07_REV001

LUMASCOPE USA INC. 1300 Industrial Rd., Unit #19 San Carlos, CA 94070, USA • Free Call: 1-866-695-LUMA(5862) • Ph: 1-(650)-595-LUMA(5862) • Fax: 1-(650)-595-5820