

1300 Industrial Road, Unit #19
San Carlos, CA 94070

Tel: 1-(650)-595-LUMA(5862)


Fax: 1-(650)-595-5820

Email: info@lumascap.com

FREE CALL 1-866-695-LUMA(5862) US & Canada

LS521A-1 Eterna

Wallmount





Specifications

Lamp source LS521A-1	2 x 20W max MR16 IRC (GU5.3)
UL classification	Suitable for wet locations
IP rating	IP56
Construction	316 marine grade stainless steel
Installation types	Wall mount
Standard inclusions	Internal glare control louver Slide & lock mounting mechanism
Ambient operating temperature	-4°F to 122°F (-20°C to +50°C)
Warranty	10 year structural, 1 year electrical
Accessories <i>Order separately</i>	LLLS Linear spreader lens LS696 Mounting plate for 4in J-Box LS697 Mounting plate for 2in x 3in single gang switch box LS643-R/G/B/Y Dichroic color filters
Photometrics	Refer to www.lumascap.com

Any luminaire can become hot - take care with appropriate use and placement




LS521A-1 Eterna




LS521A-1

LS521A-1

PRODUCT	LAMP	WATTAGE	BASE	VOLTAGE	Code
Eterna	MR16	2 X 20W IRC max	GU5.3	12V	LS521A-1



LS696 Mounting Plate
4in J-Box
0.125in (3mm) stainless steel



LS697 Mounting Plate
2in x 3in single gang switch box
supplied standard
0.125in (3mm) stainless steel