



LSLED-24V96WD277 is a 24V DC Class 2 LED Power Supply suitable for use in dry and damp locations.

**Electrical**

|                      |                               |
|----------------------|-------------------------------|
| <b>Input Voltage</b> | 120-277V, 50/60Hz             |
| <b>Output</b>        | 24V DC, 4A max                |
| <b>Efficiency</b>    | 86% typ.                      |
| <b>Connections</b>   | 6 x 1/2" entries (3 in/3 out) |

**Physical**

|                                |  |
|--------------------------------|--|
| <b>Ambient Operating Temp.</b> | -22°F to 140°F (-30°C to 60°C)                       |
| <b>Dimensions</b>              | (w)3.00" (h)1.30" (l)11.46" (w)76mm (h)33mm (l)291mm |
| <b>Mounting Length</b>         | 11.02" (280mm)                                       |

**Certification & Compliance**

|                          |         |
|--------------------------|---------|
| <b>UL Classification</b> | UL 8750 |
| <b>IP Rating</b>         | IP20    |

**Fixture Compatibility**

In order to determine the maximum number of fixtures a transformer or power supply will operate, please refer to the compatibility tables. These tables can be found in the back of the LED catalog and online.

**Indicative Circuit Diagram**

Connections to be made in parallel, in accordance with NEC and local wiring regulations.

