



The LS793LED is a compact, shallow-depth inground luminaire for applications requiring a very compact form factor, and features a 3W, 6W or 9W LED module with output similar to a 75W MR16. The compact size allows the luminaire to be used without appearing to dominate the architecture or landscape. For better control of light, a factory set tilt option is available, as well as dimming for single colour via Lumascope d5 driver technology.

### Performance

| Static White & Colour | Lumen Output (lm) |     |     | Efficacy (lm/W) |    |    | Peak Intensity (cd) |       |       |
|-----------------------|-------------------|-----|-----|-----------------|----|----|---------------------|-------|-------|
|                       | 3W                | 6W  | 9W  | 3W              | 6W | 9W | 3W                  | 6W    | 9W    |
| ● 3,000 K (80 CRI)    | -                 | 535 | 840 | -               | 74 | 82 | -                   | 6,675 | 5,300 |
| ● 4,000 K (80 CRI)    | -                 | 547 | 906 | -               | 76 | 88 | -                   | 7,349 | 5,718 |
| ● Blue (470nm)        | -                 | -   | -   | -               | -  | -  | -                   | -     | -     |

Static white lumen output values are based on a luminaire with 20° lens.

|                    |                            |
|--------------------|----------------------------|
| <b>Beam Angles</b> | 20°, 30°, 20°x40°, 40°x20° |
|--------------------|----------------------------|

### Electrical

|                       |                                               |
|-----------------------|-----------------------------------------------|
| <b>LED Power</b>      | 3W, 6W, 9W                                    |
| <b>Consumption</b>    | 7.2W (nominal for 6W), 10.2W (nominal for 9W) |
| <b>Lifetime (L70)</b> | >60,000hrs (B10, L70, TM21)                   |
| <b>Input Voltage</b>  | Low Voltage 24V DC (International Market)     |

### Control


|                  |                                                                     |
|------------------|---------------------------------------------------------------------|
| <b>Protocols</b> | PWM (0-10V to PWM, DMX to PWM and DALI to PWM converters available) |
|------------------|---------------------------------------------------------------------|

### Physical


|                                      |                                                                          |
|--------------------------------------|--------------------------------------------------------------------------|
| <b>Housing</b>                       | 316 Marine Grade Stainless Steel lid & high pressure die cast brass body |
| <b>Installation</b>                  | Direct burial - concrete, landscape, planters etc,                       |
| <b>Ambient Operating Temperature</b> | -20°C to 50°C (-4°F to 122°F)                                            |
| <b>Surface Temperature</b>           | ≤65°C (≤ 149°F) <b>HumanTouch™</b> Compliant                             |



Photometric data is based on test results from a NIST traceable testing lab. IES data is available at [www.lumascap.com](http://www.lumascap.com)  
 Note: No depreciation factor is applied to the data shown.



## Wiring Diagram - Static Colour (DMX / DALI)




### Control Protocols

|      |                                                          |
|------|----------------------------------------------------------|
| DMX  | For DMX control signal, use LS67100 DMX to PWM converter |
| DALI | For DALI control signal, use LSLED-RGBDIM-DALI converter |

### Up to 20 luminaires per run under the following conditions:

- ☐ Up to three (3) individually addressed dimmable channels
- ☐ Up to 20 luminaires per dimmable channel
- ☐ Luminaires driven by integral LED drivers
- ☐ Luminaires powered through individual power supplies or
- ☐ Luminaires powered through LS67100 PWM controller only (up to 100W total)
- ☐ Refer to 'Maximum Circuit Load' table for circuit limitations
- ☐ Always observe local electrical codes for branch circuit current limitations

## Wiring Diagram - Static Colour (0-10V)



### Control Protocols

|       |                                                               |
|-------|---------------------------------------------------------------|
| 0-10V | For 0-10V control signal, use LS6125-2 0-10V to PWM converter |
|-------|---------------------------------------------------------------|

### Up to 50 luminaires per run under the following conditions:

- ☐ Stand alone static colour dimming solution
- ☐ Up to 50 luminaires dimmed together
- ☐ Luminaires driven by integral LED drivers using LS6122 wall plate dimmer
- ☐ Luminaires powered through individual or shared power supplies
- ☐ Refer to 'Maximum Circuit Load' table for circuit limitations
- ☐ Always observe local electrical codes for branch circuit current limitations


## Maximum Circuit Load

Compatibility with each driver is indicated by the value shown in the table, representing the maximum number of luminaires that may be powered from each driver based on a maximum cable run of 100m (328ft) and a trunk cable size of 3.3mm<sup>2</sup>. Please note, this does not take into consideration voltage drop beyond a distance of 100m or ampacity limits of the branch circuit. For assistance, please consult factory.

| LSLED-24V Power Supplies |                   |      |      |
|--------------------------|-------------------|------|------|
| Input Voltage            | 100-240V, 50/60Hz |      |      |
| Output Voltage           | 24V DC            |      |      |
| Wattage                  | 40W               | 100W | 150W |
| LS793LED, 3W             | 5                 | 18   | 23   |
| LS793LED, 6W             | 3                 | 10   | 14   |
| LS793LED, 9W             | 2                 | 6    | 9    |

NOTE: The above diagrams are intended to show electrical pathways between luminaires and ancillary device. These diagrams are not intended to show type or colour of cord / wire, luminaire input voltage rating, wire gauge or approved use of the cord / wire supplied with luminaires.

## Wiring Diagram - Dynamic Colour (DMX / DALI)



## Control Protocols

## DMX

For DMX control signal, use LS67100 DMX to PWM converter

## DALI

For DALI control signal, use LSLED-RGBDIM-DALI converter

## Up to 20 luminaires per run under the following conditions:

- ☐ Up to 20 luminaires addressed and controlled together
- ☐ Luminaires driven by integral LED drivers
- ☐ Luminaires powered through individual power supplies or
- ☐ Single luminaire powered through LS67100 PWM controller
- ☐ Refer to 'Maximum Circuit Load' table for circuit limitations
- ☐ Always observe local electrical codes for branch circuit current limitations

## Maximum Circuit Load

Compatibility with each driver is indicated by the value shown in the table, representing the maximum number of luminaires that may be powered from each driver based on a maximum cable run of 100m (328ft) and a trunk cable size of 3.3mm<sup>2</sup>. Please note, this does not take into consideration voltage drop beyond a distance of 100m or ampacity limits of the branch circuit. For assistance, please consult factory.

LSLED-24V Power Supplies

| Input Voltage  | 100-240V, 50/60Hz |      |      |
|----------------|-------------------|------|------|
| Output Voltage | 24V DC            |      |      |
| Wattage        | 40W               | 100W | 150W |
| LS793LED, 3W   | 5                 | 18   | 23   |
| LS793LED, 6W   | 3                 | 10   | 14   |
| LS793LED, 9W   | 2                 | 6    | 9    |

NOTE: The above diagrams are intended to show electrical pathways between luminaires and ancillary device. These diagrams are not intended to show type or colour of cord / wire, luminaire input voltage rating, wire gauge or approved use of the cord / wire supplied with luminaires.

## Power Supply Specifications

### DC Power Supplies

#### LSLED-24V100W240

##### 24V DC Ripple Free Power Supply

|                            |                      |
|----------------------------|----------------------|
| Input                      | 170-250V AC, 50/60Hz |
| Output                     | 100W, 24V DC, 4.2A   |
| Ambient Temperature Rating | -10°C to 50°C        |
| Compliance                 | IEC61347-2-13, CE    |
| IP Rating                  | IP66                 |
| Short Circuit Protection   | Yes                  |
| Open Circuit Protection    | Yes                  |
| Protection Class           | Class II CE          |

#### LSLED-24V150W240

##### 24V DC Ripple Free Power Supply

|                            |                     |
|----------------------------|---------------------|
| Input                      | 90-305V AC, 50/60Hz |
| Output                     | 150W, 24V DC, 6.3A  |
| Ambient Temperature Rating | -10°C to 50°C       |
| Compliance                 | IEC61347-2-13, CE   |
| IP Rating                  | IP66                |
| Short Circuit Protection   | Yes                 |
| Open Circuit Protection    | Yes                 |
| Protection Class           | Class II CE         |

#### LSLED-24V40W240

##### Electronic DC Power Supply - wall mounted

|                            |                                                     |
|----------------------------|-----------------------------------------------------|
| Input                      | 100-240V AC, 50/60Hz                                |
| Rating                     | 40W / 1.67A                                         |
| Output                     | 24V                                                 |
| Ambient Temperature Rating | -25°C to 60°C (-13°F to 140°F)                      |
| Output Circuits            | 1                                                   |
| Approvals                  | CE, EN60950-1, EN61347-2-13                         |
| IP Rating                  | IP65/67                                             |
| Dimensions                 | H 171mm W 62mm L 37mm<br>(H 6.7" / W 2.4" / L 1.5") |
| Weight                     | 0.7kg (1.6lb)                                       |

## Control Related Equipment

#### LS6125-2

##### 0-10V to PWM translator - wall mounted

|                            |                                                      |
|----------------------------|------------------------------------------------------|
| Input                      | 100-240V AC, 50/60Hz                                 |
| Rating                     | 20W / 0.83A                                          |
| Output                     | 24V                                                  |
| Ambient Temperature Rating | -10°C to 50°C                                        |
| Open Circuits              | 1                                                    |
| Control Protocol           | 0-10V                                                |
| Approvals                  | CE                                                   |
| IP Rating                  | IP65/67                                              |
| Dimensions                 | H 204mm W 166mm L 91mm<br>(H 8.0" / W 6.5" / L 3.6") |
| Weight                     | 0.5kg (1.1lb)                                        |

#### LS67100

##### DMX to PWM translator

|               |                                                        |
|---------------|--------------------------------------------------------|
| Input         | 24V DC                                                 |
| Rating        | 4 x 60W max                                            |
| Output        | 4 x 2.5A max                                           |
| Open Circuits | 4                                                      |
| Approvals     | CE, UL                                                 |
| IP Rating     | IP65                                                   |
| Dimensions    | H 286mm W 117mm L 82mm<br>(H 11.25" / W 4.6" / L 3.2") |
| Weight        | 0.2kg (0.5lb)                                          |


**Control Related Equipment cont...**

## LSLED-RGBDIMDALI

## DALI converter

|                            |                                             |
|----------------------------|---------------------------------------------|
| Input                      | 24V DC                                      |
| Rating                     | 30W max                                     |
| Output                     | 24V DC PWM (Inverted)                       |
| Ambient Temperature Rating | 50°C                                        |
| Output Channels            | 3                                           |
| Control Protocol           | DMX512A, DALI, DSI, RDM                     |
| Approvals                  | CE Ctick EN6137-1 , EN61347-2-13, IEC 62384 |
| IP Rating                  | IP67                                        |
| Weight                     | 0.75kg                                      |

## Wiring Diagram - Static Colour (0-10V)




## Control Protocols

|       |                                                                |
|-------|----------------------------------------------------------------|
| 0-10V | For 0-10V control signal, use LS6133<br>0-10V to PWM converter |
|-------|----------------------------------------------------------------|

## Wiring Diagram - Static Colour

Please note: The use of a GFCI may be required. Consult local wiring rules.



## Maximum Circuit Load


Compatibility with each transformer or power supply is indicated by the value shown in the table, representing the maximum number of luminaires that may be powered from each transformer or power supply. Please note, this does not take into consideration voltage drop or ampacity limits of the branch circuit. In addition, dimming circuit total wire length must be kept under 328' (100m). For assistance, please consult factory.

|                | Transformer / Power Supplies |                  |                  |                               |      |      |                   |      |      |
|----------------|------------------------------|------------------|------------------|-------------------------------|------|------|-------------------|------|------|
|                | LS-TWM-1-300                 | LSLED-24V75W277  | LSLED-24V96WD277 | LSLED-24V 120 / 240 / 320 P09 |      |      | LS6520            |      |      |
| Input Voltage  | 120V, 60Hz                   | 120-277V 50/60Hz | 120-277V 50/60Hz | 120-277V 50/60Hz              |      |      | 100-277V, 50/60Hz |      |      |
| Output Voltage | 12/13/14V, 60Hz              | 24V DC           | 24V DC           | 24V DC                        |      |      | 24V DC            |      |      |
| Wattage        | 1 x 300W circuit             | 75W              | 96W              | 120W                          | 240W | 320W | 120W              | 240W | 320W |
| LS793LED, 3W   | 42                           | 13               | 21               | 25                            | 52   | 70   | 25                | 52   | 70   |
| LS793LED, 6W   | 23                           | 6                | 12               | 14                            | 29   | 39   | 14                | 29   | 39   |
| LS793LED, 9W   | 15                           | 4                | 8                | 9                             | 19   | 26   | 9                 | 19   | 26   |

NOTE: The above diagrams are intended to show electrical pathways between luminaires and ancillary device. These diagrams are not intended to show type or colour of cord / wire, luminaire input voltage rating, wire gauge or approved use of the cord / wire supplied with luminaires.



### Wiring Diagram - Dynamic Colour (DMX) for 12-15V AC Circuit




#### Control Protocols

DMX

For DMX control signal, use LS67100  
DMX to PWM converter

### Wiring Diagram - Dynamic Colour (DMX) for 24V DC Circuit



#### Control Protocols

DMX

For DMX control signal, use LS67100  
DMX to PWM converter

### Maximum Circuit Load

Compatibility with each transformer or power supply is indicated by the value shown in the table, representing the maximum number of luminaires that may be powered from each transformer or power supply. Please note, this does not take into consideration voltage drop or ampacity limits of the branch circuit. In addition, dimming circuit total wire length must be kept under 328' (100m). For assistance, please consult factory.

|                | Transformer / Power Supplies |                  |                  |                               |      |      |                   |      |      |
|----------------|------------------------------|------------------|------------------|-------------------------------|------|------|-------------------|------|------|
|                | LS-TWM-1-300                 | LSLED-24V75W277  | LSLED-24V96WD277 | LSLED-24V 120 / 240 / 320 P09 |      |      | LS6520            |      |      |
| Input Voltage  | 120V, 60Hz                   | 120-277V 50/60Hz | 120-277V 50/60Hz | 120-277V 50/60Hz              |      |      | 100-277V, 50/60Hz |      |      |
| Output Voltage | 12/13/14V, 60Hz              | 24V DC           | 24V DC           | 24V DC                        |      |      | 24V DC            |      |      |
| Wattage        | 1 x 300W circuit             | 75W              | 96W              | 120W                          | 240W | 320W | 120W              | 240W | 320W |
| LS793LED, 3W   | 42                           | 13               | 21               | 25                            | 52   | 70   | 25                | 52   | 70   |
| LS793LED, 6W   | 23                           | 6                | 12               | 14                            | 29   | 39   | 14                | 29   | 39   |
| LS793LED, 9W   | 15                           | 4                | 8                | 9                             | 19   | 26   | 9                 | 19   | 26   |

NOTE: The above diagrams are intended to show electrical pathways between luminaires and ancillary device. These diagrams are not intended to show type or colour of cord / wire, luminaire input voltage rating, wire gauge or approved use of the cord / wire supplied with luminaires.

## Transformer / Power Supply Specifications

### Class 2 LED Power Supplies

#### LSLED-24V96WD277

##### Electronic DC Power Supply - wall mounted

|                            |                                                       |
|----------------------------|-------------------------------------------------------|
| Input                      | 120-277V, 50/60Hz                                     |
| Output                     | 24V DC, 4A max                                        |
| Efficiency                 | 86% typ.                                              |
| Ambient Temperature Rating | -22°F to 140°F (-30°C to 60°C)                        |
| Connections                | 6 x 1/2" entries (3 in / 3 out)                       |
| UL Classification          | UL 8750                                               |
| Location                   | Dry / Damp location only                              |
| IP Rating                  | IP66 (NEMA 3)                                         |
| Dimensions                 | H 1.3" W 3.0" L 11.46"<br>(H 33mm / W 76mm / L 291mm) |

### Low Voltage DC Power Supplies

#### LS6520

##### Power Unit for Wet Locations

|                 |                                                        |
|-----------------|--------------------------------------------------------|
| Input           | 100-277V, 50/60Hz                                      |
| Output          | 24 or 30V DC                                           |
| Output Circuits | 1                                                      |
| Approvals       | UL2108, CSA C22.2 No. 250.0                            |
| IP Rating       | IP65, suitable for wet locations                       |
| Dimensions      | H 5.3" W 13.4" D 9.3"<br>(H 134mm / W 341mm / D 236mm) |
| Weight          | 13.2lb (6.0kg)                                         |

#### LSLED-24V240WP09

##### Electronic DC Power Supply - wall mounted

|                            |                                                                         |
|----------------------------|-------------------------------------------------------------------------|
| Input                      | 120-277V, 50/60Hz                                                       |
| Rating                     | 240W                                                                    |
| Output                     | 24V or 30V                                                              |
| Ambient Temperature Rating | -40°F to 122°F (-40°C to 50°C)                                          |
| Connections                | 2 x 3/4" entries (power in / out)<br>2 x 3/4" entries (low voltage out) |
| UL Classification          | ANSI / UL2108 Wet Location Listed                                       |
| Location                   | Dry / Damp / Wet locations                                              |
| IP / NEMA Rating           | 1, 3R, 4X, 6P, 12                                                       |
| Dimensions                 | H 5.22" W 13.41" D 11.43"<br>(H 133mm / W 341mm / D 290mm)              |
| Weight                     | 10.9lb (5.0kg)                                                          |

#### LSLED-24V75W277

##### Electronic DC Power Supply - wall mounted

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| Input                      | 120-277V, 50/60Hz                                       |
| Output                     | 24V DC, 3.13A, (0.05A min)                              |
| Efficiency                 |                                                         |
| Ambient Temperature Rating | -40°F to 140°F (-40°C to 60°C)                          |
| Connections                | 2 x 1/2" entries (in / out)                             |
| UL Classification          | Class 2, UL1012 / 1585, UL1310                          |
| Location                   | Dry / Damp / Wet locations                              |
| IP Rating                  | IP66 (NEMA 3)                                           |
| Dimensions                 | H 1.67" W 2.95" L 11.22"<br>(H 42mm / W 75mm / L 285mm) |

#### LSLED-24V120WP09

##### Electronic DC Power Supply - wall mounted

|                            |                                                                         |
|----------------------------|-------------------------------------------------------------------------|
| Input                      | 120-277V, 50/60Hz                                                       |
| Rating                     | 120W                                                                    |
| Output                     | 24V or 30V                                                              |
| Ambient Temperature Rating | -40°F to 122°F (-40°C to 50°C)                                          |
| Connections                | 2 x 3/4" entries (power in / out)<br>2 x 3/4" entries (low voltage out) |
| UL Classification          | ANSI / UL2018, CSA C22.2 No. 250.0 - Listed Power Unit                  |
| Location                   | Dry / Damp / Wet locations                                              |
| IP / NEMA Rating           | 1, 3R, 4X, 6P, 12                                                       |
| Dimensions                 | H 4.47" W 11.35" D 9.41"<br>(H 120mm / W 288mm / D 293mm)               |
| Weight                     | 7.5lb (3.4kg)                                                           |

#### LSLED-24V320WP09

##### Electronic DC Power Supply - wall mounted

|                            |                                                                         |
|----------------------------|-------------------------------------------------------------------------|
| Input                      | 120-277V, 50/60Hz                                                       |
| Rating                     | 320W                                                                    |
| Output                     | 24V or 30V                                                              |
| Ambient Temperature Rating | -40°F to 104°F (-40°C to 40°C)                                          |
| Connections                | 2 x 3/4" entries (power in / out)<br>2 x 3/4" entries (low voltage out) |
| UL Classification          | ANSI / UL2108 Wet Location Listed                                       |
| Location                   | Dry / Damp / Wet locations                                              |
| IP / NEMA Rating           | 1, 3R, 4X, 6P, 12                                                       |
| Dimensions                 | H 5.22" W 13.41" D 11.43"<br>(H 133mm / W 341mm / D 290mm)              |
| Weight                     | 12.1lb (5.5kg)                                                          |

## Transformers for Landscape Lighting Applications

### LS-TWM-1-300

Magnetic Transformer - wall mounted

|                 |                                                         |
|-----------------|---------------------------------------------------------|
| Input           | 120V                                                    |
| Rating          | 300W                                                    |
| Output          | 12 / 13 / 14 / 15V                                      |
| Output Circuits | 1                                                       |
| Protection      | Electrostatic shield, magnetic breaker                  |
| Approvals       | UL, CUL                                                 |
| NEMA Rating     | 3R                                                      |
| Construction    | Stainless steel                                         |
| Dimensions      | H 17.6" W 6.8" D 6.19"<br>(H 447mm / W 173mm / D 157mm) |
| Weight          | 27lb (12.3kg)                                           |

## Control Related Equipment

### LS6133

0-10V to PWM translator - NEMA enclosure required (by others)

|                 |                                                   |
|-----------------|---------------------------------------------------|
| Input           | 24V DC                                            |
| Rating          | 96W max                                           |
| Output          | 4A max                                            |
| Output Circuits | 1                                                 |
| Approvals       | UL, CUL Recognised, Class 2                       |
| IP Rating       | IP66                                              |
| Dimensions      | H 5.2" W 1.3" D 1"<br>(H 132mm / W 33mm / D 25mm) |
| Weight          | 0.2lb (0.1kg)                                     |

### LSLED-24V12W277

Electronic DC Power Supply - NEMA enclosure required (by others)

|                 |                                                       |
|-----------------|-------------------------------------------------------|
| Input           | 120-277V, 50/60Hz                                     |
| Rating          | 12W / 0.5A                                            |
| Output          | 24V DC                                                |
| Output Circuits | 1                                                     |
| Approvals       | UL, CUL Recognized, Class 2                           |
| IP Rating       | IP66                                                  |
| Location        | Wet location                                          |
| Dimensions      | H 3.35" W 1.42" D 0.91"<br>(H 85mm / W 36mm / D 23mm) |
| Weight          | 0.282lb (0.1kg)                                       |